

Pressure Switch - 24Series

CE



	PART NUMBER	Setting Range (in bar)	Tolleranza (in bar)	Max Over Pr. limit(in bar)	Max Working Pressure(in bar)
Diaphragm Low Pressure	24 0 0 6 2 1	0.3 to 5	± 0.15	300	150
	24 0 0 6 2 2	1 to 10	± 0.5		
	24 0 0 6 2 3	10 to 25	± 1		
	24 0 0 6 2 4	25 to 80	± 2.5		
piston High Pressure	24 0 0 6 1 5	50 to 200	± 2 ÷ 10	800	450
	24 0 0 6 1 6	100 to 300	± 4 ÷ 12		
	24 0 0 6 1 7	200 to 400	± 4 ÷ 15		

- Case : Anodized Aluminium
- Threaded Fitting : Zinc Plated Steel
- Max switches current : 5(1)A
- Max fluid temperature : 120°C
- Mechanical working life : 10⁶ Diaphragm, 10⁵ Piston Version
- Protection Degree : IP65 (DIN43650)
- Process connection : 1/4" BSP Male, others on request
- Hysteresis : 10 to 30% of setting value (Diaphragm)
: 10 to 40% of setting value (Piston)
- Weight : 190 gms



HTA INSTRUMENTATION (P) LTD.,

An ISO 9001: 2015 Certified Company & NABL Accredited Calibration Laboratory as per ISO/IEC 17025:2017

Your One Stop For Instrumentation Supply, Automation & Calibration

73, Ramachandra Agrahara, Near T.R. Mills, Chamarajpet, Bangalore - 560018, INDIA.

Phone : 080-26749750, 26759253, 26740681 E-mail : sales@htaipl.com Website : www.htaipl.com



Certificate No. IQSC202010014