

# Pressure Switch - 28Series

CE



Part Number	Setting Range (in bar)	Tolerance @ 20°C (in bar)	Max Over Pressure limit(in bar)	Max Working Pressure (in bar)
28 N 0 6 1 6	30 to 150	$\pm 2 \div 10$	800	450
28 N 0 6 1 7	100 to 300	$\pm 5 \div 15$		

- Case : Zinc plated steel
- Electric Contact : Silver Plated
- Max Switches Current : 6(1)A / 250 VAC
- Max Fluid Temperature : 80°C
- Mechanical Working Life : 10<sup>5</sup> Operations
- Protection Degree
  - a) with cap 3015001 : IP 54
  - b) with Din Cap 3900001 : IP 65 (Din Cap)
  - c) with Connector 3900003 : IP 65
- Hysteresis : 30 to 50% of setting value Adjustable
- Process connection : 1/4" BSP Male, others on request
- Seal : NBR
- Weight : 115 gms.



**HTA INSTRUMENTATION (P) LTD.,**

An ISO 9001: 2015 Certified Company & NABL Accredited Calibration Laboratory as per ISO/IEC 17025:2017

**Your One Stop For Instrumentation Supply, Automation & Calibration**

# 73, Ramachandra Agrahara, Near T.R. Mills, Chamarajpet, Bangalore - 560018, INDIA.

Phone : 080-26749750, 26759253, 26740681 E-mail : sales@htaipl.com Website : www.htaipl.com



ISO 9001:2015 CERTIFIED  
Certificate No. IQSC202010014