

Digital RTD Thermometer

NEW

FEATURES:

- LCD with Back-light
- Max / Min / Avg Temperature Recording
- Dual Channel Display (C 372)
- Switchable Measuring Units °C or °F
- Auto Power Off
- Battery Life Indicator
- Data Hold Function

SPECIFICATION:

- | | |
|------------------------|---|
| ■ Display | : 4 Digit LCD |
| ■ Input Sensor Type | : Pt100, Pt500, Pt1000 (Selectable) |
| ■ Measurement Range | : -100°C ~ 300°C |
| ■ Resolution | : 0.1°C |
| ■ Accuracy | : $\pm 0.1\%$ rdg $\pm 0.4^\circ\text{C}$ |
| ■ Probe Input Socket | : Pt 100 probe - Din 4 Pin socket |
| ■ Sampling Rate | : 2 times per sec. |
| ■ Water Resistance | : IP 67 |
| ■ Power Supply | : 3 $\times$ 1.5VDC AAA Battery |
| ■ Operating Temp. | : 0 to 50°C |
| ■ Battery | : Approx 100hrs with Alkaline Battery |
| ■ Dimension | : 150 $\times$ 66 $\times$ 31 mm |
| ■ Weight | : 175gms |
| ■ Standard Accessories | : Pt100 Probe & Instruction Manual |



Model: C 370



HTA INSTRUMENTATION (P) LTD.,

An ISO 9001: 2015 Certified Company & NABL Accredited Calibration Laboratory as per ISO/IEC 17025:2017

Your One Stop For Instrumentation Supply, Automation & Calibration

73, Ramachandra Agrahara, Near T.R. Mills, Chamarajpet, Bangalore - 560018, INDIA.

Phone : 080-26749750, 26759253, 26740681 E-mail : sales@htaipl.com Website : www.htaipl.com

