


Pocket COND./TEMP. METER



Boiler Water



Cooling Water



Water Treatment



Process Water



Drinking Water



Swimming Pool



Aquaculture



Waste Water

Features

- Big Lcd Dual Display
- IP65 Water Proof
- Stability Indication
- Quick Response
- Auto Temperature Compensation
- One Touch Auto-Calibration
- Auto Ranging or Manual Ranging
- Calibration Values are Adjustable
- 20 Mins Auto Power off
- Simple Sleep Mode Disable
- Data Hold Function
- Low Battery Indicator
- Temperature Unit Selectable

Specifications

Cond. Range	0~1999uS or 0~19.99mS
Cond. Accuracy	+/-1%FS +/- 1 digit
Cond. Resolution	1uS or 0.01mS
Temp. Range	0~50.0 °C
Temp. Accuracy	+/-0.5 °C
Temp.Resolution	0.1
ATC	ATC
LCD Size	30(H)x18(W)mm
Operating Temp.	0~50 °C
Operating RH%	Humidity < 80%
Storage Temp.	0~60 °C
Storage RH%	Humidity < 90%
Sensor life Time	>6 months (with good maintenance)
Dimension	165(L)x35(W)x32(H)mm
Weight	115g
Battery	LR44 x 4pcs
Standard Package	Meter/Battery/Manual/Paper box

Equinox™



Model : EQ-8351



HTA INSTRUMENTATION (P) LTD.,

An ISO 9001: 2015 Certified Company & NABL Accredited Calibration Laboratory as per ISO/IEC 17025:2017

Your One Stop For Instrumentation Supply, Automation & Calibration

73, Ramachandra Agrahara, Near T.R. Mills, Chamarajpet, Bangalore - 560018, INDIA.

Phone : 080-26749750, 26759253, 26740681 E-mail : sales@htaipl.com Website : www.htaipl.com



ISO 9001:2015 CERTIFIED
Certificate No. IQSC202010014