

# DIGITAL PARTICLE COUNTER

## with TFT Color LCD Display

**Equinox™**

**EQ-9880/9881** are Particle Counter with 2.8" color TFT LCD display & a micro SD memory card for capturing images for viewing in your PC, providing fast easy and accurate readings for particle counter, GAS(HCHO, CO) Detectors, air temperature & relative humidity measurements. It is the first combination of these measurements in global, would be the best instrument for environment protection and energy save. The dewpoint temperature measurements and dataanalyzing, the real scene and time can be displayed on color TFT LCD. Any memory readings can be recorded in SD card the user can be back in office to analyze the measured air quality under the support of software.

## FEATURES

- 2.8"TFT 320x240 pixels color LCD display
- Simultaneously measure & display 6 channel of particle sizes, measure particle size down to 0.3  $\mu\text{m}$
- GAS (HCHO, CO) DETECTORS
- Air Temperature and Humidity, dewpoint & wet bulb temperature
- Max, Min, DIF, AVG record, Date/time setup controls, alarm
- Micro SD(MAX. use 8GB)memory card, Bluetooth / USB interface
- Auto Power Off
- Selectable sample time, count data, programmable delay
- Store 5000 records of date, time, counts, relative humidt, temperature, sample volumes, alarms and location label
- Language selection English, Chinese, French, German, Spaish



## SPECIFICATIONS

**EQ-9880 / 9881**

| Particle Counter               |  | 9880 | 9881 |
|--------------------------------|--|------|------|
| Channel                        | 0.3, 0.5, 1.0, 2.5, 5.0, 10 $\mu\text{m}$                    | *    | *    |
| Flow Rate                      | 0.1ft <sup>3</sup> (2.83L / min) controlled by internal pump | *    | *    |
| Count Modes                    | Totalize, Concetration, Audio                                | *    | *    |
| Coincidence Loss               | 5%, 2,000,000 partcils per ft <sup>3</sup>                   | *    | *    |
| <b>Air Temperature Measure</b> |  |      |      |
| Air Temp. Range                | 0 ~ 50 °C/32 to 122 °F; Basic Accuracy : $\pm 0.5$ °C/ °F    | *    | *    |
| Humidity Range                 | 0 ~ 100%RH; Basic Accuracy : $\pm 2.5\%$ RH (20%-80%RH)      | *    | *    |
| Dew Point Temp. Range          | -30 ~ 100°C / -22-199 °F                                     | *    | *    |
| Wet Bulb Temp. Range           | 0 ~ 80 °C/32 ~ 176 °F  | *    | *    |
| <b>GAS Detectors</b>           |  |      |      |
| HCHO( Methanal) Range          | 0.01 ~ 5.00ppm; Basic Accuracy: $\pm 5\% \pm 0.01$ ppm       |      | *    |
| CO (Carbon Monoxide) Range     | 0 ~1000ppm ; Basic Accuracy : $\pm 5\% \pm 10$ ppm           |      | *    |
| Size                           | 240mm x 75mm x 57mm  |      |      |
| Weight                         | 570g   |      |      |



**HTA INSTRUMENTATION (P) LTD.,**

An ISO 9001: 2015 Certified Company & NABL Accredited Calibration Laboratory as per ISO/IEC 17025:2017

**Your One Stop For Instrumentation Supply, Automation & Calibration**

# 73, Ramachandra Agrahara, Near T.R. Mills, Chamarajpet, Bangalore - 560018, INDIA.

Phone : 080-26749750, 26759253, 26740681 E-mail : sales@htaip.com Website : www.htaip.com

