

AC/DC True RMS Clamp Meter

Features

- TRUE RMS
- Auto ranging
- Auto Power Off
- High Speed Bargraph
- DATA HOLD Function
- PEAK HOLD Function



SPECIFICATIONS

Display	: 3.3/4 digital display (Max. reading 3999)
Sampling Rate	: 2 times /sec. (reading) 20 times/Sec. (analog bar indication)
Battery	: 9V battery
Dimensions	: 242 × 66 × 36mm
Weight	: approx. 500g
Jaw Opening Diameter	: 35mm (210/211), 40mm

Model : C 212

Function	Range	Resolution	Accuracy
ACA	0 ~ 1000A	0.01A ~ 0.1A	± 1.9%rdg + 5dghts
DCA	0 ~ 1000A	0.01A ~ 1A	± 2%rdg + 5dghts
ACV	0 ~ 750V	0.1V ~ 1V	± 1.2%rdg + 5 dghts
DCV	0 ~ 1000V	0.1V ~ 1V	± 0.75%rdg + 2dghts
Ohms	0 ~ 4000Ω	0.1Ω ~ 1Ω	± 1%rdg + 2dghts
Hz (A)	0 ~ 10KHz	1 Hz	± 0.1%rdg + 1dghts
Hz (V)	0 ~ 10KHz	1 Hz	± 0.1%rdg + 1dghts
»»»	Active Sound Level : ≤ 50Ω		
→	0.2V		



HTA INSTRUMENTATION (P) LTD..

An ISO 9001: 2015 Certified Company & NABL Accredited Calibration Laboratory as per ISO/IEC 17025:2017

Your One Stop For Instrumentation Supply, Automation & Calibration

73, Ramachandra Agrahara, Near T.R. Mills, Chamarajpet, Bangalore - 560018, INDIA.

Phone : 080-26749750, 26759253, 26740681 E-mail : sales@htaipl.com Website : www.hhtaipl.com



ISO 9001:2015 CERTIFIED

Certificate No. IQSC202010014