

REFRIGERANT LEAKAGE DETECTOR (with Air Pump)

C 382 is a perfect tool for Air-condition system maintaining. The operation interface is intuitive with button, light bar and sound. The "Air Sucking System" greatly help the sensitivity and response time. The "Auto-Reset" function can help the operator to distinguish the leaking spot among the already spreading refrigerant while maintain high sensitivity.

Model : C 382

CE



FEATURES :

- Microprocessor Control with advanced digital signal processing
- Multi Color Visual Display
- High - Med - Low Sensitivity Selector
- Low Battery Indication
- Semiconductor Gas Sensor
- Detection of R-134a, R-410A, R-407C, R22... Freon Gas
- Carrying Case Included
- 15.5" (40 cm) Flexible Stainless Probe
- Reference Leak Source Included
- Ambient Concentration Reset
- Long Life, DC Brushless Fan
- Variable Intensity Audible and Visual Alarms



HTA INSTRUMENTATION (P) LTD.,

An ISO 9001: 2015 Certified Company & NABL Accredited Calibration Laboratory as per ISO/IEC 17025:2017

Your One Stop For Instrumentation Supply, Automation & Calibration

73, Ramachandra Agrahara, Near T.R. Mills, Chamarajpet, Bangalore - 560018, INDIA.

Phone : 080-26749750, 26759253, 26740681 E-mail : sales@htaipl.com Website : www.htaipl.com



ISO 9001:2015 CERTIFIED
Certificate No. IQSC202010014