

NOISE DOSE METER

Equinox™



EQ - ST - 130

SPECIFICATIONS

Display	Single LCD MAX Reading 999999
Display Refresh Rate	1 Time / sec
Microphone	½" Electret Condenser Microphone
Measurement Items	Does%, Lxyp, Lxmax, Lxeq, SEL(LAE), Peak, LAVG, TWA, LEP, LN%
Measurement Range	30db to 130dB (A)
	35dB to 130dB (C)
	40dB to 130dB (Z)
Dynamic Range	60dB
Accuracy	±1.5dB @ 94dB 1 KHZ
Environmental Conditions	Temp. : 23 °C ±5 °C, Humidity : <80%
Internal Memory	MAX Dataloger Data : 10000
Time Weighting	Fast, Slow, Impulse, Peak
Frequency Weighting	A / C / Z
Frequency Range	20Hz ~ 8KHZ
Starting Time	<10 Second
Battery life	9V Battery
Dimensions	285 (L) X 90(W) X 39 (H) mm



HTA INSTRUMENTATION (P) LTD.,

An ISO 9001: 2015 Certified Company & NABL Accredited Calibration Laboratory as per ISO/IEC 17025:2017

Your One Stop For Instrumentation Supply, Automation & Calibration

73, Ramachandra Agrahara, Near T.R. Mills, Chamarajpet, Bangalore - 560018, INDIA.

Phone : 080-26749750, 26759253, 26740681 E-mail : sales@htaipl.com Website : www.htaipl.com



ISO 9001:2015 CERTIFIED
Certificate No. IQSC202010014