

RTD DINRAIL MOUNT TEMPERATURE TRANSMITTER

Equinox™

• Features :

- ✧ Easy to Mount.
- ✧ Fine ZERO and SPAN Adjustments Enable user to set up 4~20mA Output.
- ✧ High Accurate and Low Cost.
- ✧ ABS Construction with Watertight Enclosure.
- ✧ Most Economical & Rugged.



Model : EQ-TR 5

• GENERAL SPECIFICATIONS :

Input	3 Wire RTD Sensor
Output current	4-20mA DC
Range	0~50°C, 0~100°C, 0~200°C 0~400°C, -50~+50°C other Ranges upon request
Input type	3-Wire Pt100Ω
Accuracy (at 25°C)	±0.25%
Power supply	24VDC
Load capability	600Ω Max, @ 24VDC
Operating temperature range	-20 to + 50°C
Weight	Approx, 50g



HTA INSTRUMENTATION (P) LTD.,

An ISO 9001: 2015 Certified Company & NABL Accredited Calibration Laboratory as per ISO/IEC 17025:2017

Your One Stop For Instrumentation Supply, Automation & Calibration

73, Ramachandra Agrahara, Near T.R. Mills, Chamarajpet, Bangalore - 560018, INDIA.

Phone : 080-26749750, 26759253, 26740681 E-mail : sales@htaipl.com Website : www.htaipl.com

