

RTD BULK HEAD TEMPERATURE TRANSMITTER

Equinox®

Model : EQ-TR 4



• Features :

- Easy to Mount.
- Fine ZERO and SPAN Adjustments Enable user to set up 4~20mA Output.
- High Accurate and Low Cost.
- ABS Construction with Watertight Enclosure.
- Most Economical & Rugged.

• GENERAL SPECIFICATIONS :

Input	3 Wire RTD Sensor
Output current	4-20mA DC
Range	0~50 °C, 0~100 °C, 0~200 °C 0~400 °C, -50~+50 ° C other Ranges upon request
Input type	3-Wire Pt100
Accuracy (at 25 °C)	±0.25%
Power supply	24VDC
Load capability	600 Max, @ 24VDC
Operating temperature range	-20 to + 50 °C
Dimensions	44.5dia × 27mm (1.75 × 1.06)Height includes terminal ship
Weight	Approx, 30g (1.1 oz)



HTA INSTRUMENTATION (P) LTD.,

An ISO 9001: 2015 Certified Company & NABL Accredited Calibration Laboratory as per ISO/IEC 17025:2017

Your One Stop For Instrumentation Supply, Automation & Calibration

73, Ramachandra Agrahara, Near T.R. Mills, Chamarajpet, Bangalore - 560018, INDIA.

Phone : 080-26749750, 26759253, 26740681 E-mail : sales@htaipl.com Website : www.htaipl.com

