

DIGITAL VIBRATION METER

Equinox

Features :

- Specially designed for easy on site Vibration measurement of all rotating machinery for quality Control, commissioning, and predictive maintenance purposes.
- High quality Accelerometer for accurate and repeatable measurements
- Bearing condition monitoring function
- LCD digital display
- Lightweight and easy to use
- Wide frequency range (10Hz. to 10kHz.) in Acceleration mode
- Automatic power shut off to conserve power.



EQ-VM6320

Specifications :

- Display : 4 digits, 18 mm LCD
- Transducer : Piezoelectric Accelerometer
- Measuring Parameter : Velocity, Acceleration, and Displacement
- **Measuring Range** :
- Acceleration (Peak) : 0.1-200m/s², 10Hz to 1kHz
- Velocity(RMS) : 0.1-200mm/s, 10Hz to 1kHz; 10Hz to 10kHz
- Displacement (Peak to Peak) : 0.001-2.0mm, 10Hz to 1kHz
- Accuracy : ± 5%+2 digits
- Output : AC output 2.0V peak full scale (load resistance: above 10k)
- Power supply : 4 × 1.5 AA size
- Operating conditions : Temperature : 0 ~ 50 °C
Humidity : Below 90% RH
- Dimensions : 61 × 69 × 32mm
- Weight : 240g including batteries
- **Accessories included** : Powerful Rare Earth Magnet 1 pc.
Carrying Case..... 1 pc.
Operation Manual..... 1 pc.



HTA INSTRUMENTATION (P) LTD.,

An ISO 9001: 2015 Certified Company & NABL Accredited Calibration Laboratory as per ISO/IEC 17025:2017

Your One Stop For Instrumentation Supply, Automation & Calibration

73, Ramachandra Agrahara, Near T.R. Mills, Chamarajpet, Bangalore - 560018, INDIA.

Phone : 080-26749750, 26759253, 26740681 E-mail : sales@htaipl.com Website : www.htaipl.com



ISO 9001:2015 CERTIFIED
Certificate No. IQSC202010014