

# Pressure Switch - XP 600Series

CE



Model Type	Setting Interval	Test Pressure	Fix Differential
<b>XP600</b>	0.2 to 1.2 bar	4 bar	0.3 + / - 0.15 bar
	0.5 to 1.5 bar	5 bar	0.3 + / - 0.15 bar
	1 to 2.5 bar	6 bar	0.35 + / - 0.15 bar
	2 to 6 bar	10 bar	0.35 + / - 0.2 bar

## Specification

- Pressure Connection - brass
- Thread - 1/4" BSP
- Main Body - Techno Polymer
- Membrane and Sealing - AISI316 and silicon
- Protection Degree - IP00
- Adjustment - by screw
- Electric Intervention - SPDT
- Electric Connection - Terminal 6.3 × 0.8
- Admitted Temperature - 125°C
- Burst Pressure - higher than 20 bar
- Thermic Drift - 0.04 bar for 10°C with respect to Temperature of + 20°C



**HTA INSTRUMENTATION (P) LTD.,**

An ISO 9001: 2015 Certified Company & NABL Accredited Calibration Laboratory as per ISO/IEC 17025:2017

**Your One Stop For Instrumentation Supply, Automation & Calibration**

# 73, Ramachandra Agrahara, Near T.R. Mills, Chamarajpet, Bangalore - 560018, INDIA.

Phone : 080-26749750, 26759253, 26740681 E-mail : sales@htaipl.com Website : www.htaipl.com

