FLASH LINK REUSABLE TEMPERATURE & HUMIDITY USB DATA LOGGER CFR21





Product Specifications :









Laboratory / R&D

Pharmaceutical

Green House

Refrigeration Vans

Ware Housing

Fruits & Vegetables

Measurement Range	-40°C to 50°C (-40°F to 122°F)
Temperature Accuracy	0.5°C (±1°F) at 32°F to 150°F (0°C to 50°C) 1°C (±2°F) (-40°C to 0°C)
Temperature Resolution	0.1°C / °F
Humidity Range	1% to 99% RH
Humidity Accuracy	±3% at 50% RH at 25°C
Data Capacity	21,000 data points
Data Download Time	5 seconds typical for 3800 points
Programmable Alarm Levels	High & Low levels over entire range displayed on LCD
Battery	Coin Cell Lithium
Dimensions/Body	1.57 in x 3.66in x 0.94in (87mm x 50mm x 15mm)
Casing	ABS plastic
Weight	1.4 oz. (39.7 grams)
Shock Resistance	Withstands 3-foot (1 meter) drop to hard surface
Certification	CE Mark, NIST traceable, RoHS Compliant
Display	LCD, Red LED Alarm
Waterproof Rating	IP56 (with silicon cap on)
Storage conditions	-4°F to 122°F (-20°C to 50°C) 0% to 95% RH w/o condensation
System Requirements	Windows PC with current Operating System, Adobe Reader
Programming	FlashPDF Program Manager Software
Download Requirements	Direct USB connection to PC





Note : CFR21 Software at additional charges

Model: 20248

- Dual Channel, Temperature & Humidity
- · Ideal for monitoring ambient Temperature & Humidity
- User Programmable : Manual or auto start, logging intervals, high / low alarms
- Large easy-to-read LCD
- Multi-language FlashPDF Program Manager software
- Summary analysis of data, with alarm information
- Degree Minutes and MKT calculations



An ISO 9001: 2015 Certified Company & NABL Accredited Calibration Laboratory as per ISO/IEC 17025:2017 Your One Stop For Instrumentation Supply, Automation & Calibration # 73, Ramachandra Agrahara, Near T.R. Mills, Chamarajpet, Bangalore - 560018, INDIA. Phone : 080-26749750, 26759253, 26740681 E-mail : sales@htaipl.com Website : www.htaipl.com

