

04 Channel Temperature Datalogger

For K / J / E / T Type Thermocouple Input

Model: C378

Features

- Auto Range
- PC Interface
- LED Back Light
- Four Channel Input
- Four Channel Display
- Resolution 0.1°C / 0.1 °F
- With Windows Software
- Auto shut off for battery saving
- 16,000 Records Data Logger each channel
- Isolated input protection up to 250 Vac between any two inputs




LED Back Light




Specifications

Measurement Range	-200°C ~ 1372°C (K Type) -328°F ~ 2501 °F (K Type)
Accuracy	-200°C ~ 1372°C ...±0.1% rdg+0.7°C -328°F ~ 2501°F...±0.1% rdg +0.7°C
Battery Type	9V Battery
Operating Condition	-10°C to 50°C (<90%RH)
Storage condition	-40°C to 60°C (>75%RH)
Dimensions	197mm X 65mm X 36mm
Weight	310g
Accessories	Battery, Operation Manual, Carrying Case Bead Type Temperature Probe TP-K01 X 2Pcs USB Cable, Software

Four Channel Display



T1-T2 Display



HTA INSTRUMENTATION (P) LTD.,

An ISO 9001: 2015 Certified Company & NABL Accredited Calibration Laboratory as per ISO/IEC 17025:2017

Your One Stop For Instrumentation Supply, Automation & Calibration

73, Ramachandra Agrahara, Near T.R. Mills, Chamarajpet, Bangalore - 560018, INDIA.

Phone : 080-26749750, 26759253, 26740681 E-mail : sales@htaipl.com Website : www.htaipl.com

