

## 4-in-1 Precision Humidity & Temperature Meter

**EQ - 3215** has been designed to measure the combination of Humidity, Temperature, Dew point and wet Bulb Temperature. Sensor type is a calibrated digital output from a single chip Relative Humidity & Temperature sensor.

## **Features**

- Dual Display
- High Resolution 0.01°C / 0.01% RH
- Fast response and High Accuracy
- Dew Point & Wet Bulb Temperature Measurement
- LCD with Back Light
- Max / Data & Hold Function
- Auto Power-off
- Low Battery Indication



**Model: EQ-321S** 

## **Specifications**

Display	4 ½ digit LCD
Measuring Range	RH : 0 to 100%
	Temperature : -30°C to 100°C
	Dew Point Temperature : -30°C to 100°C
	Wet Bulb Temperature : 0 to 80°C
Accuracy RH	±2%RH (at 25°C, 20 to 80%RH), ±2.5%RH (at other ranges)
Temp.	±0.5°C (at 25°C) , ±0.8°C (at other ranges)
Resolution	RH: 0.01% RH, Temp.: 0.01°C
Response Time	10 Sec.
Auto Power Off	After 15 min. of Inactivity
Sampling Rate	2.5 samples per sec
<b>Operating Condition</b>	0 to 40°C < 80% RH non Condensing
Storage Condition	-10 to 60°C < 80% RH non Condensing
Power Supply	9V Battery
Size ( H X W X D )	255 × 45 × 34 mm
Weight	200gms





