

APPLICATION

- To Measure the RPM of a Rotating object
- To Inspect the Defect on any Rotating Surface
- Printing Industries



MODEL-DT-2350PB

SPECIFICATIONS

| | |
|-------------------------|------------------------------------|
| Measurement Range (FPM) | 50-40,000 FPM |
| Accuracy | $\pm(0.05\%n+1d)$ |
| Ranges of Measurement | High & Low |
| Flash Adjust | Coarse Adjustment, Fine Adjustment |
| | X2 and $\div 2$ for fast check |
| Flash Tube lifetime | 1 Million times |
| Resolution | 0.1/1FPM |
| Triggering Mode | Interior / Exterior |
| Power Supply | 230 V AC |
| Dimension | 215x85x180mm |
| Weight | 1000g |
| Standard package List | Main Unit |
| | Carrying case |
| | Instruction manual |
| Optional Accessories | Flash Tube |



HTA INSTRUMENTATION (P) LTD.,

An ISO 9001: 2015 Certified Company & NABL Accredited Calibration Laboratory as per ISO/IEC 17025:2017

Your One Stop For Instrumentation Supply, Automation & Calibration

73, Ramachandra Agrahara, Near T.R. Mills, Chamarajpet, Bangalore - 560018, INDIA.

Phone : 080-26749750, 26759253, 26740681 E-mail : sales@htaipl.com Website : www.htaipl.com



ISO 9001:2015 CERTIFIED
Certificate No. IQSC202010014