

Pressure Switch - 40Series

CE



Normally Open Contact Type	Normally Closed Contact Type	Setting Range (in bar)	Tolerance @ 20°C (in bar)	Max Over Pressure limit(in bar)	Max Working Pressure (in bar)
40 1 0 H 1 6	40 2 0 H 1 6	50 to 150	$\pm 2 \div 10$	800	450
40 1 0 H 1 7	40 2 0 H 1 7	100 to 300	$\pm 5 \div 15$		

- Case : Zinc Plated Steel
- Electric contact : Silver
- Max fluid temperature : 100°C
- Mechanical working life : 10^5 Operations
- Protection degree
 - a) with cap 3015001 : IP 54
 - b) with Din cap 3900001 : IP 65 (Din Cap)
 - c) with Connector 3900200 : IP 65
- Process connection : 1/4" BSP Male, others on request
- Seal : NBR + Teflon
- Piston : AISI 303
- Weight : 75 gms



HTA INSTRUMENTATION (P) LTD.

An ISO 9001: 2015 Certified Company & NABL Accredited Calibration Laboratory as per ISO/IEC 17025:2017

Your One Stop For Instrumentation Supply, Automation & Calibration

73, Ramachandra Agrahara, Near T.R. Mills, Chamarajpet, Bangalore - 560018, INDIA.

Phone : 080-26749750, 26759253, 26740681 E-mail : sales@htaipl.com Website : www.hhtaipl.com



ISO 9001:2015 CERTIFIED
Certificate No. IQSC202010014