

# 4-20mA Portable Datalogger

Self contained Datalogger for recording the current in a 4-20 mA loop. 4-20mA Can be configured for any parameter recording like temperature, RH, Pressure, etc.,

## Features

- Over/ Under Alarm Settings
- User Selectable Recording Start
- Tamper Proof
- Data Rollover Option
- Graphic or Text Data
- Windows based software



## Model : L420



## Application

- Automated Test Systems
- Manufacturing
- Data Recording for Sensor Outputs

## SPECIFICATIONS

Input Current Range	4-20mA
Current Accuracy	$\pm 0.05\text{mA}$
Current Resolution	0.01mA
Storage Points	21,500 points
Sampling Rate	Variable between 1 sec to 18 hrs
Time Accuracy	$\pm 1000$ ppm
Calibration	Single point offset calibration thru software.
Battery	9V Battery
Operating Temp	0 to 60°C

**Optional Accessories :** Data Acquisition Software - Logit LLS

## Features

- PC Software on CD ROM
- Lint Interface
- Cable for Serial Port
- Data Exportable to Text or Excels
- Graphic & Text Data
- Real time Monitoring
- Password Protected for Calibration
- Compatible with Win 95 & above



**HTA INSTRUMENTATION (P) LTD.,**

An ISO 9001: 2015 Certified Company & NABL Accredited Calibration Laboratory as per ISO/IEC 17025:2017

**Your One Stop For Instrumentation Supply, Automation & Calibration**

# 73, Ramachandra Agrahara, Near T.R. Mills, Chamarajpet, Bangalore - 560018, INDIA.

Phone : 080-26749750, 26759253, 26740681 E-mail : sales@htaipl.com Website : www.htaipl.com

